A3 Colour MFP

MP C6503 MP C8003





# MP C6503/MP C8003

#### **GENERAL**

Warm-up time:

38 seconds First output speed: Full colour: 7.5/6.3 seconds

B/W: 5.5/4.7 seconds

Continuous output speed: Full colour: 65/80 pages per minute

B/W: 65/80 pages per minute

Intel Atom Processor Bay Trail:

1.91 GHz Standard: 4 GB

HDD: 640 GB

Dimensions (W x D x H): 750 x 880 x 1,225 mm

Weight: 250 kg

Power source 220 - 240 V, 50/60 Hz

**COPIER** 

Memory

Copying process

4-Drum Dry Electrostatic Transfer System with internal transfer belt

Up to 9,999 copies Multiple copying:

Resolution: 600 dpi

From 25% to 400% in 1% steps Zoom:

**PRINTER** 

Printer language: Standard: PCL5e, PCL6, PDF Direct

Option: Genuine Adobe ®PostScript®3™, XPS, IPDS

Print resolution: 1,200 x 4,800 dpi

Standard: SD slot, Wireless LAN (IEEE

802.11b/g/n), Bluetooth, Ethernet 10 base-T/100 base-TX/1000 base-T USB2.0, NFC Tag, USB Host Option: Ethernet 10 base-T/100 base-TX. Bi-directional IEEE 1284. Wireless LAN (IEEE 802.11a/b/g/n), USB 2.0

Network protocol: TCP/IP (IP v4, IP v6)

Windows® Vista, Windows® 7, Windows® environments:

Windows® 8, Windows® 8.1, Windows® 10. Windows® Server 2008, Windows® Server 2008R2, Windows® Server 2012, Windows®

Server 2012R2

Mac OS environments: Macintosh OS X v10.7 or later

UNIX environments: UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux, IBM®

AIX

SAP® R/3® environments: SAP® R/3®

AS/400® using OS/400 Host Print Other supported environments:

Transform, IBM iSeries

### **SCANNER**

Max. 120 (simplex)/220 (duplex) Scanning speed: originals per minute

Resolution: Maximum: 600 dpi A3, A4, A5, B4, B5, B6 Original size: Bundled drivers: Network TWAIN

E-mail, Folder, USB, SD card, SMB,

FTP, mobile device (with a free App)

**FAX** 



www.ricoh-europe.com

PSTN, PBX ITU-T (CCITT) G3 Compatibility:

Standard: 8 x 3.85 line/mm. 200 x 100 Resolution:

Detail: 8 x 7.7 line/mm, 200 x 200 dpi Super fine: 8 x 15.4 line/mm, 400 x 400

dpi, 16 x 15.4 line/mm, 400 x 400 dpi

Compression method: MH, MR, MMR, JBIG

G3: 2 second(s) (200 x 100 dpi, JBIG), Transmission speed: 3 second(s) (200 x 100 dpi, MMR)

Maximum: 33.6 Kbps Modem speed: Standard: 4 MB Memory capacity: Maximum: 8 MB

## PAPER HANDLING

SRA3, A3, A4, A5, A6, B4, B5, B6 Recommended paper size:

Paper input capacity: Standard: 3,500 sheets (with optional

finisher)

Maximum: 8,100 sheets Standard: 500 sheets Paper output capacity:

Maximum: 3,500 sheets

Paper tray(s): 52.3 - 256 g/m<sup>2</sup> Paper weight: A4 LCT: 52.3 - 300 g/m<sup>2</sup>

Bypass tray: 52.3 - 300 g/m<sup>2</sup> Duplex: 52.3 - 256 g/m<sup>2</sup> A3/DLT LCT: 52.3 - 300 g/m<sup>2</sup>

#### **ECOLOGY**

Power consumption: Maximum: 2,400 W

Ready mode: 198/199 W Low power mode: 181/182 W Sleep mode: Less than 0.89 W TEC (Typical Electricity Consumption):

4 8/6 2 kWh

# **OPTIONS**

2,000-sheet large capacity tray, A4/LT large capacity tray, 2,200 sheet SRA3 LCT, 3,000-sheet finisher with 65-sheet stapler, 3,000-sheet finisher with 100-sheet stapler, 2.000-sheet booklet finisher, Punch kits, 9-bin mailbox, Cover interposer, Tab Sheet Holder, Copy tray, Jogger unit, Plockmatic booklet maker™, GBC Streampunch™ Ultra, Bi-directiona IEEE 1284, Wireless LAN (IEEE 802.11a/b/g/n), PostScript3, IPDS unit, Counter interface. File format converter. Card reader bracket. Fax Connection Unit, Fax memory, Fax option, Multi folding unit, Unicode Font Package for SAP, OCR Unit, Cooling Fan Unit, Enhanced security HDD, External keyboard bracket, NFC Card Reader, Banner paper tray guide, G3 Interface unit, Extended USB board, Card Reader Cover

### **CONSUMABLES**

Black: 47,000 prints Toner capacity:

Cyan: 26,000 prints Magenta: 26,000 prints Yellow: 26,000 prints

For availability of models, options and software, please consult your

local supplier.























RICOH @Remote

ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2016 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.